



Ifor Williams Trailers

GH 1054BT Plant Hire Trailer

Technical Specification



Specification and Features

- Galvanized steel chassis, panels and framework
- 24mm phenolic coated laminate platform
- Spring assisted ramp with integrated ramp supports
- Raised bucket rest with bucket lip
- Ifor Williams beam axles (Two), parabolic leaf spring suspension system
- Sealed for life unitized wheel bearings
- 185/70R13 tyres
- Tyre Pressure 6 Bar (87PSI)
- Full regulation lighting with detachable lighting cable
- 12v/24v LED Lights
- Step-on steel treadplate mudguards
- Heavy duty jockey wheel
- Five pairs of 500kg lashing points (welded) per trailer
- Three pairs of 500kg lashing points (bolt-on) per trailer
- 40mm coupling eye
- Security marking and registration with The Equipment Register (T.E.R.)

Applications

Suitable for transporting a wide selection of plant, including tracked excavators, and many items of wheeled equipment such as rollers and a variety of access platforms

Key Dimensions

Gross Weight	Unladen Weight	Payload	Internal Width	Internal Length	Overall Length	Overall Width	Loading Height	Tow eye height (laden)	Loading Angle
3500kg	660kg	2840kg	1625mm / 5'4"	3045mm / 9'11"	5010mm / 16'6"	2090mm / 6'11"	350mm / 1'4"	394mm / 1'4"	13°to15°during loading

